

# RP series



- Denti e lame intercambiabili
- Interchangeable teeth and blades
- Dents et lames interchangeables
- Dientes y cuchillas intercambiables

- Optional rotazione rinforzata con doppio motore
- Optional reinforced rotation with double motor
- Optional rotation renforcée avec double moteur
- Rotación reforzada opcional con doble motor

Abbinamento ideale escavatore-attrezzatura  
Ideal excavator-attachment matching  
Association idéale excavateur-outil  
Combinación ideal excavadora-implemento

Abbinamento ammesso escavatore-attrezzatura  
Permitted excavator-attachment matching  
Association autorisée excavateur-outil  
Combinación permitida excavadora-implemento

ton	11	12	15	16	15	16	20	21	20	21	25	26	25	26	34	35	32	35	42	45
-----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

		RP 10	RP 13	RP 20	RP 25	RP 30
 kg	kg	1035	1420	2060	2665	3170
A	mm	563	605	650	825	860
B	mm	1824	1962	2113	2442	2466
C	mm	380	415	540	550	610
F1	t	190	190	235	295	370
F2	t	60	60	80	95	120
	mm	180	180	220	260	260
 bar	bar	350	350	350	350	350
 l/min.	l/min.	180/250	180/250	180/250	200/300	250/350
 bar	bar	140	140	140	140	140
 l/min	l/min	15/30	15/30	20/40	20/40	25/50

