

SG

series






- Disponibile con chele da demolizione
- Available with demolition jaws
- Disponible avec mâchoires de démolition
- Disponibile con garras de demolición
- Rotazione rinforzata con doppio motore a partire da SG15
- Reinforced rotation with double motor starting from SG15
- Rotation renforcée avec double moteur à partir de SG15
- Rotación reforzada con doble motor a partir de SG15

Abbinamento ideale escavatore-attrezzatura
Ideal excavator-attachment matching
Association idéale excavateur-outil
Combinación ideal excavadora-implemento

Abbinamento ammesso escavatore-attrezzatura
Permitted excavator-attachment matching
Association autorisée excavateur-outil
Combinación permitida excavadora-implemento

ton	1,5	2	5	6	4	5	8	9	5	6	10	11	12	13	22	24	17	20	27	30	25	26	35	38
-----	-----	---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----

		SG03	SG06	SG08	SG15	SG20	SG30
	kg	140 - 140*	340 - 355*	460 - 490*	980 - 1040*	1280 - 1340*	2080 - 2150*
A	mm	75	1007	1427	1880	2125	2255
B	mm	300	450	550	845	940	1250
C	mm	910	1235	1305	1500	1605	1647
D	mm	540	825	990	1105	1285	1353
E	mm	900	1250	1400	1295	1795	1814
	n°	1	1	1	1	2	2
	bar	160 - 180	180 - 200	180 - 200	180 - 200	200 - 220	200 - 220
	l/min.	30 - 35	35 - 40	45 - 50	100 - 120	160 - 180	180 - 200
	bar	100 - 120	120 - 140	120 - 140	100 - 120	120 - 140	120 - 140
	l/min	15 - 18	15 - 19	15 - 20	25 - 30	30 - 45	30 - 45

* Versione con chele da demolizione - Version with demolition jaws - Version avec mâchoires de démolition - Versión con garras de demolición

